



Cooling System Refilling Gun

Dramatically reduces filling time and eliminates airlocks in cooling system

Features

- Utilizes deep vacuum technology to eliminate airlocks during cooling system refilling
- Eliminates the need for system bleeding
- Universal attachment to most radiator and header tanks
- Small & large rubber cones to suit both passenger & commercial vehicles; no additional adapters needed
- Eliminates coolant spills and waste
- Integrated vacuum gauge automatically tests cooling system for leaks
- Integrated filling tap and vacuum check valve removes the need for interchanging hoses
- Quick release air supply locking trigger for easy use

NOTE: Does not drain coolant from system

Specifications

Air Pressure: Min: 550kpa (80psi). Max: 900kpa (130psi)
Air Consumption: Max 180 ltr/min (10CFM) at 100psi.
Vacuum: 25" in Hg (-0.85bar) at 100psi.
Gauge: 0-30" in Hg (0 to -1.0bar)
Thread connection: 1/4" BSP. (airline fitting not included)
Filling Hose Length: 1500mm

CONTENTS: QUICKFILL GUN, VACUUM GAUGE, 1500MM HOSE, SMALL & LARGE RUBBER CONES, HOSE, MANUAL AND CASE



PATENTED

Part No: 70880



SpeedyVac 3-Step Operation

1. Drain old coolant from cooling system.
2. Couple to system and connect shop air. Operate trigger to create deep vacuum and release trigger to test for leaks.
3. Insert hose into new coolant container. Turn system tap to 'FILL' position to refill with new coolant.



PBT USA Inc

13795 Rider Trail North
Suite #109
Earth City, MO 63045
USA

Phone: 314 219 0999
Fax: 314 219 0097
Toll Free: 877 PBT USA4
877 728 8724

Internet: www.pbtusa.com
Email: sales@pbtusa.com

PBT Australia Pty Ltd

A.B.N. 72 067 983 475
13/121 Kerry Road
Archerfield QLD 4108
Australia

Phone: +61 7 3274 3800
Fax: +61 7 3275 3251
Internet: www.pbtusa.com
Email: sales@pbtusa.com